



PRECISE TEMPERATURE, HUMIDITY, BAROMETRIC PRESSURE TRANSMITTERS with Ethernet interface
 temperature * barometric pressure * relative humidity * dew point temperature * absolute humidity * specific humidity * mixing ratio * specific enthalpy



- APPLICATIONS**
- server rooms
 - telecommunication devices
 - warehouses
 - glasshouses
 - manufacturers
 - museums, archives, galleries
 - air-conditioned rooms

Ethernet sensor is designed for measurement of temperature, barometric pressure, relative humidity, dew point temperature, absolute humidity, specific humidity, mixing ratio or specific enthalpy. Degrees Celsius and Fahrenheit are user selectable.

Large dual line LCD for simultaneous display of temperature, pressure or relative humidity or other calculated humidity interpretation is an advantage. Display is possible to switch off. State-of-the-art capacitive polymer sensor ensures excellent calibration long term stability, inertia against water and condensation. Transmitter is designed for use in non-aggressive environment.

MODES OF COMMUNICATION

| | |
|-------------|--|
| ModBus TCP: | Modbus TCP protocol enables to read measured values, set alarm limits, adjust the probe, read firmware version. |
| Telnet: | Port 9999 enables to set alarm limits (lower and upper limits for T, RH, Tdp, hysteresis and time delay), e-mail addresses, SNMP addresses, probe description, refresh of www pages (10s to 65535s), select type of www pages, set storing interval to history (10s to 65535s), enable each communication channel. Capacity of the history memory is 100 sets of measured temperature, humidity, pressure+computed value. Password protection of this port is enabled. Automatic IP address assignment from DHCP server is also enabled. |
| www pages: | User selectable design of www pages enabling to display curves of measurement history. User can design the look of www pages and select values to display. |
| SNMP: | It is possible to read actual values and alarm limits. In case of alarm creation warning message (trap) is sent to IP addresses defined by the user (maximum three addresses). |
| SOAP: | Transmitter enables to send actual measured data in the format of SOAP message to selected web server in preset interval 10-65535 s. In case message is not received by the server till next message is sent, warning trap 1/2 is sent. |

ALARM OPTIONS

| | |
|------------|---|
| E-mail: | In case of alarm creation warning e-mail message is sent to addresses defined by the user (maximum three addresses). |
| www pages: | In case of exceeding adjusted limits of measured values active alarm is displayed at www page. |
| SNMP: | In case of alarm creation warning message (trap) is sent to IP addresses defined by the user (maximum three addresses). |
| syslog: | Transmitter enables to send text messages to selected syslog server after different events appear. E.g. after transmitter restart, alarm activation, communication error with SNTP, write to transmitter via mdb, sntp, after firmware change, after alarm termination, after communication error with SOAP server. |

TECHNICAL PARAMETERS

| | |
|--|--|
| Accuracy of temperature measurement: | ±0.4 °C, accuracy of temperature transducer T4511 is ±0.2 °C |
| Supported temperature units: | degrees Celsius, degrees Fahrenheit |
| Range and accuracy of relative humidity: | 0 to 100%, accuracy ±2.5% relative humidity from 5 to 95% at 23 °C |
| Accuracy and range of dew-point temperature: | ±1,5 °C at ambient temperature T < 25 °C and RH>30%, rozsah -60 až +80 |
| Accuracy of absolute humidity measurement: | ±3g/m ³ at ambient temperature T < 40 °C, range 0 to 400 g/m ³ |
| Accuracy of specific humidity measurement: | ±2g/kg at ambient temperature T < 35 °C, range 0 to 550 g/kg |
| Accuracy of mixing ratio measurement: | ±2g/kg at ambient temperature T < 35 °C, range 0 to 995 g/kg |
| Accuracy of specific enthalpy measurement: | ± 3kJ/kg at ambient temperature T < 25 °C, range: 0 to 995 kJ/kg |



PRECISE TEMPERATURE, HUMIDITY, BAROMETRIC PRESSURE TRANSMITTERS with Ethernet interface

temperature * barometric pressure * relative humidity * dew point temperature *
absolute humidity * specific humidity * mixing ratio * specific enthalpy

| TECHNICAL PARAMETERS - continuance | |
|--|---|
| Accuracy and range of barometric pressure: | ±1.3hPa at 23 °C, range 600 to 1100hPa |
| Supported pressure units: | hPa, kPa, mbar, mmHg, inHg, inH ₂ O, PSI, oz/in ² |
| Operating temperature range of the case: | -30 to +80 °C |
| Operating temperature range of LCD display: | readable to +70 °C, it is recommended to switch OFF the LCD over +70 °C |
| Range of temper. compensation of RH sensor: | -30 to +105 °C |
| Filtering ability of sensor cover: | 0.025mm |
| Protection: | case with electronics IP30, T+RH probe IP40 |
| LAN connector: | RJ-45 connector |
| Power: | 9-30Vdc, maximum consumption 1W |
| Power over Ethernet: | for power over Ethernet any PoE splitter is necessary - e.g. D-Link DWL-P50 |
| Power connector: | co-axial, diameter 5.5 x 2.1 mm |
| Mechanical dimensions of the case (W x H x D): | 89 x 73 x 37 mm |

AVAILABLE MODELS OF TRANSMITTERS:

| TYPE | MEASURED VALUE | MAXIMUM MEASURING RANGE OF TEMP., PRESSURE | DESCRIPTION |
|-------|--|---|--|
| T4511 | temperature | -200 to +600 °C | Temperature transducer for external probes with Pt1000/3850ppm sensor (not included), accuracy of the input ±0.2 °C |
| T2514 | barometric pressure | 600 to 1100hPa accuracy: ±1,3hPa at 23 °C | Barometer - Reading and pressure output in these units: hPa, kPa, mbar, mmHg, inHg, inH ₂ O, PSI, oz/in ² Barometer enables to measure sea level pressure by setting of correction to altitude above sea level. |
| T3511 | temperature humidity | -30 to +105 °C* probe, cable + 80 °C max, optionally with cable up to +105 °C | Thermometer-hygrometer. T+RH probe with 1m cable. Cable lengths 2m or 4m available optionally. Measured values are also converted to other humidity interpretation - dew point temperature, absolute humidity, specific humidity, mixing ratio or specific enthalpy. |
| T7511 | temperature humidity barometric pressure | -30 to +105 °C* probe, cable + 80 °C max, optionally with cable up to +105 °C Pressure: 600 to 1100hPa accuracy: ±1,3hPa at 23 °C | Thermometer-hygrometer-barometer. T+RH probe with 1m cable. Cable lengths 2m or 4m available optionally. Pressure sensor is located in the control unit with display. Measured values are also converted to other humidity interpretation - dew point temperature, absolute humidity, specific humidity, mixing ratio or specific enthalpy. Reading and pressure output in these units: hPa, kPa, mbar, mmHg, inHg, inH ₂ O, PSI, oz/in ² Barometer enables to measure sea level pressure by setting of correction to altitude above sea level. |

Relative humidity at temperature over +85 °C is limited in accordance with the graph. Near plastic case with electronics maximum temperature is +80 °C.

Included accessory:

Traceable calibration certificate from the manufacturer, instruction manual. Calibration certificate with declared metrological traceability of etalons is based on requirements of EN ISO/IEC 17025 standard.

Free program TSensor for configuring of the transmitter is ready to download from www.cometsystem.cz.

Free program SensorReader for logging values from one thermometer to a PC disk file is ready to download. Recorded values in CSV format are easy to process in e.g. Excel.

For acquiring values from several transmitters, third party software is necessary to use. Tested functionality is with programs TIRS.NET, ControlWeb, EasyView.

For record of values to graphs via web interface, project Cacti www.cacti.net is available.

Optional accessory: - see further

